



-NOTE-

1) ALL WELDS SHOULD BE GROUND AND POLISHED SMOOTH TO A #3 (150 GRIT) FINISH.

- 2) ALL ROUGH EDGES SHOULD BE CLEANED OF ANY BÚRR'S.

3) ALL ANGLES ARE AT 90' UNLESS OTHERWISE NOTED.
4) ALL RADIUS AND CORNERS ARE TO BE A 1/32 UNLESS OTHERWISE NOTED.

REMOVE BURRS AND SHARP EDGES TOLERANCES UNLESS OTHERWISE NOTED: LAYOUT, 2 HD CI PAIL FILLER (SEMI- AUTO) ANGLES ±0'-30' FRACTIONS ±1/32 DECIMALS:
.X ±.030
.XX ±.010
.XXX ±.005

ODEN MACHINERY, INC. 199 FIRE TOWER DRIVE TONAWANDA, NEW YORK USA 14150 PHONE (716)—874—3822 TOLL FREE (800)—858—3822 FAX (716)—874—3000

THIS MATERIAL IS THE EXCLUSIVE PROPERTY OF ODEN MACHINERY, INC. ANY DUPLICATION, RETENTION OR TRANSMITTAL TO OTHERS IS PROHIBITED WITHOUT PRIOR CONSENT.

DRFT DATE ENGR SHEET DRAWING NO.

DCM 4/30/20 DCM 1 of 1 1"=20" MATERIAL 304 S.S.

OM1034-392